



333 RT. 17 N.
Mahwah, NJ 07430
800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

TOOL MODEL: J-GUN AIR-1 APACHE DUAL SPEED
J1P00747

PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	341	47	462
25	1.72	422	58	572
30	2.07	503	70	682
35	2.41	584	81	792
40	2.76	665	92	902
45	3.10	739	102	1002
50	3.45	813	112	1102
55	3.79	886	123	1202
60	4.14	960	133	1302
65	4.48	1034	143	1402
70	4.83	1108	153	1502
75	5.17	1181	163	1602
80	5.52	1255	174	1702

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use $\frac{1}{2}$ " or $\frac{3}{4}$ " diameter hose for optimal results; minimum diameter hose to be used is $\frac{1}{2}$ ".

1/23/2015

www.TORCGUN.COM

V5.5 01/14/2015

LOOK US UP ON FACEBOOK AND TWITTER"