



333 RT. 17 N.
 Mahwah, NJ 07430
 800-FOR-HYTORC

**TOOL MODEL: J-GUN AIR-2 APACHE DUAL SPEED
 J2P00024**

PRESSURE / TORQUE CONVERSION CHART

PRESSURE		Standard Torque		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	520	72	706
25	1.72	635	88	861
30	2.07	749	104	1016
35	2.41	864	119	1171
40	2.76	979	135	1327
45	3.10	1089	151	1476
50	3.45	1198	166	1624
55	3.79	1307	181	1772
60	4.14	1416	196	1920
65	4.48	1518	210	2059
70	4.83	1616	223	2191
75	5.17	1713	237	2323
80	5.52	1811	250	2455
85	5.86	1919	265	2602
90	6.21	2039	282	2764

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

www.TORCGUN.COM

V5.1 09/16/2014

10/3/2014

LOOK US UP ON FACEBOOK AND TWITTER"