



333 RT. 17 N.
Mahwah, NJ 07430
800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

**TOOL MODEL: J-GUN AIR .5 APACHE DUAL SPEED
JP5P00287**

PRESSURE / TORQUE CONVERSION CHART

Standard Torque using Silencer Kit

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	129	18	175
25	1.72	149	21	202
30	2.07	169	23	229
35	2.41	189	26	257
40	2.76	209	29	284
45	3.10	229	32	310
50	3.45	248	34	336
55	3.79	267	37	362
60	4.14	286	40	388
65	4.48	306	42	415
70	4.83	326	45	442
75	5.17	346	48	469
80	5.52	366	51	496
85	5.86	386	53	523
90	6.21	406	56	550

Torque values determined using 8 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

www.TORCGUN.COM

V5.1 09/16/2014

11/3/2014

LOOK US UP ON FACEBOOK AND TWITTER"