



333 RT. 17 N.
Mahwah, NJ 07430
800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

TOOL MODEL: J-GUN AIR-5 APACHE DUAL SPEED

J5P00248

PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	1215	168	1648
25	1.72	1518	210	2059
30	2.07	1822	252	2470
35	2.41	2125	294	2882
40	2.76	2429	336	3293
45	3.10	2729	377	3700
50	3.45	3028	419	4106
55	3.79	3328	460	4512
60	4.14	3627	501	4917
65	4.48	3910	541	5301
70	4.83	4184	578	5673
75	5.17	4458	616	6044
80	5.52	4732	654	6416
85	5.86	5007	692	6789

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use ½" or ¾" diameter hose for optimal results; minimum diameter hose to be used is ½".

11/25/2014

www.TORCGUN.COM

LOOK US UP ON FACEBOOK AND TWITTER"

V5.2 11/19/2014