



333 RT. 17 N.
 Mahwah, NJ 07430
 800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

**TOOL MODEL: J-GUN AIR-2
 J200087**

PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	521	72	706
25	1.72	647	89	877
30	2.07	774	107	1049
35	2.41	901	125	1222
40	2.76	1028	142	1394
45	3.1	1155	160	1566
50	3.45	1281	177	1737
55	3.79	1408	195	1908
60	4.14	1534	212	2080
65	4.48	1634	226	2215
70	4.83	1730	239	2346
75	5.17	1827	253	2477
80	5.52	1927	266	2610
85	5.86	2059	285	2792

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

3/29/2016

www.TORCGUN.COM

LOOK US UP ON FACEBOOK AND TWITTER

V6.2 01/25/2016