



333 RT. 17 N.

Mahwah, NJ 07430

800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

TOOL MODEL: J-GUN AIR-5

J501075

PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	1150	159	1559
25	1.72	1465	203	1987
30	2.07	1781	246	2414
35	2.41	2096	290	2842
40	2.76	2412	333	3270
45	3.1	2733	378	3705
50	3.45	3054	422	4141
55	3.79	3376	467	4577
60	4.14	3698	511	5013
65	4.48	4020	556	5451
70	4.83	4343	600	5888
75	5.17	4665	645	6325
80	5.52	4984	689	6757
85	5.86	5266	728	7139

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

3/18/2016

www.TORCGUN.COM

LOOK US UP ON FACEBOOK AND TWITTER

V6.2 01/25/2016