



333 RT. 17 N.
Mahwah, NJ 07430
800-FOR-HYTORC

CERTIFICATE OF CALIBRATION

TOOL MODEL: J-GUN AIR-8 SINGLE SPEED
J800434
PRESSURE / TORQUE CONVERSION CHART

Standard Torque

PRESSURE		TORQUE		
psi	bar	ft-lbs	kgf-m	N-m
20	1.38	1743	241	2364
25	1.72	2225	308	3017
30	2.07	2714	375	3680
35	2.41	3204	443	4344
40	2.76	3693	511	5007
45	3.1	4152	574	5630
50	3.45	4608	637	6247
55	3.79	5063	700	6865
60	4.14	5519	763	7482
65	4.48	5904	816	8005
70	4.83	6280	868	8514
75	5.17	6655	920	9023
80	5.52	7037	973	9540
85	5.86	7480	1034	10142
90	6.21	7924	1095	10743

Torque values determined using 10 ft length hose

Calibrations are per ISO5393 Soft Joint Standard.

NOTE: 1) Minimum 30 CFM air required to use this pneumatic torque tool. 2) Use 1/2" or 3/4" diameter hose for optimal results; minimum diameter hose to be used is 1/2".

3/3/2016

www.TORCGUN.COM

V6.2 01/25/2016

LOOK US UP ON FACEBOOK AND TWITTER