

HYTORC

TOOL MODEL:HY-STEALTH 14 with HEX LINK

PRESSURE/TORQUE CONVERSION CHART

Standard Torque Chart

| PRESSURE IN | TORQUE IN | | | PRESSURE IN |
|--------------------|------------------|------------|-----------|--------------------|
| PSI | FT. LBS. | KGM | NM | BAR |
| 1500 | 2105 | 291 | 2854 | 104 |
| 1600 | 2247 | 311 | 3047 | 110 |
| 1800 | 2532 | 350 | 3433 | 124 |
| 2000 | 2817 | 390 | 3819 | 138 |
| 2200 | 3102 | 429 | 4205 | 152 |
| 2400 | 3386 | 468 | 4590 | 165 |
| 2600 | 3671 | 508 | 4976 | 179 |
| 2800 | 3955 | 547 | 5362 | 193 |
| 3000 | 4240 | 586 | 5748 | 207 |
| 3200 | 4525 | 626 | 6134 | 220 |
| 3400 | 4810 | 665 | 6520 | 234 |
| 3600 | 5094 | 705 | 6906 | 248 |
| 3800 | 5379 | 744 | 7292 | 262 |
| 4000 | 5664 | 783 | 7678 | 276 |
| 4200 | 5948 | 823 | 8063 | 290 |
| 4400 | 6232 | 862 | 8449 | 303 |
| 4600 | 6517 | 901 | 8834 | 317 |
| 4800 | 6801 | 941 | 9219 | 331 |
| 5000 | 7085 | 980 | 9604 | 345 |
| 5200 | 7372 | 1020 | 9993 | 358 |
| 5400 | 7659 | 1059 | 10382 | 372 |
| 5600 | 7945 | 1099 | 10771 | 386 |
| 5800 | 8232 | 1139 | 11160 | 400 |
| 6000 | 8519 | 1178 | 11548 | 414 |
| 6200 | 8805 | 1218 | 11936 | 427 |
| 6400 | 9091 | 1257 | 12324 | 441 |
| 6600 | 9377 | 1297 | 12711 | 455 |
| 6800 | 9663 | 1336 | 13099 | 468 |
| 7000 | 9949 | 1376 | 13487 | 482 |
| 7200 | 10237 | 1416 | 13878 | 496 |
| 7400 | 10525 | 1456 | 14268 | 510 |
| 7600 | 10814 | 1496 | 14659 | 524 |
| 7800 | 11102 | 1535 | 15050 | 538 |
| 8000 | 11390 | 1575 | 15440 | 552 |
| 8200 | 11676 | 1615 | 15828 | 565 |
| 8400 | 11962 | 1654 | 16216 | 579 |
| 8600 | 12248 | 1694 | 16603 | 593 |
| 8800 | 12534 | 1733 | 16991 | 607 |
| 9000 | 12820 | 1773 | 17379 | 620 |
| 9200 | 13107 | 1813 | 17768 | 634 |
| 9400 | 13394 | 1852 | 18157 | 648 |
| 9600 | 13681 | 1892 | 18546 | 662 |
| 9800 | 13968 | 1932 | 18935 | 676 |
| 10000 | 14255 | 1971 | 19324 | 690 |